

PS2 ECHO CLASSIC



MAIN CHARACTERISTICS / PERFORMANCE

ENGINE

Manufacturer Rotax
Model 912ULS/S2
Power 100 hp
Number of Cylinders 4

PROPELLER

Manufacturer Tonini
Model GT
Number of Blades 2
Type Fixed

WEIGHTS

Maximum Take-off weight 1320 lbs. Standard Equipped weight 520 lbs. Standard Useful Load 620 lbs. Limit Loads +4/-2g Ultimate Loads +6/-3g

DIMENSION

Wing Span 29.5 ft.
Wing Area 129 sq. ft.
Fuselage Length 21 ft.
Fuselage Height 8.2 ft.
Baggage Allowance 44 lbs.

SPEED

Max. at Sea Level, Gross Weight 113 kts Cruise, 75% Power 108 kts Vne 138 kts

STALL SPEED

Flaps up, Power off 36 kts Flaps down, Power off 26 kts

Rate of Climb at Sea Level 1200 ft/m
Service Ceiling 14,800 ft.
Takeoff run over 50 ft. Obstacle 820 ft.
Landing run over 50 ft. Obstacle 853 ft.
Demonstrated crosswind 20 kts

PECHO CLASSIC

S ECHO CLASSIC



Magnetic Compass

Airspeed Indicator - Kts

Altimeter Dual Mode - IN/Mb

Vertical Speed

Bank Indicator

Flap Indicator

Pitot System

Static System

Stabilator Trim Positiion Indicator

ENGINE INSTRUMENTS

Tachometer

Hour Recorder

Oil Pressure

Oil Temperature

Cylinder Head Temperature

Fuel Pressure

Voltmeter

LH + RH Fuel Quantity

FLIGHT CONTROLS

Hydraulic Toe Brakers

Parking Brake

Electric Flaps

Dual Flight Controls

Steerable Noise Wheel

Stabilitor Trim (electricaly acutuated from stick)

Engine Controls

- Dual Throttle
- Choke

Flight Trim Controls

• Stabilator (electricaly acutuated from stick)

Fuel Control Selector with on/off

Panel Switches

- Split Master Switch
- Avionics Master

Starter Key

ELECTRICAL SYSTEM

18 Amp. Hour Battery 12 Volt Alternator - 20 Amp.

Switches

- Landing Light
- Strobe Light

• Nav. Light 12 Volt Socket

Circuit Breaker Panel

FUEL SYSTEM

2 Integral Fuel Tanks (24 gal.) Total Capacity

- Engine Driven Fuel Pump
- Fuel Quick Drains
- Fuel Gascolator

INTERIOR

Pilot and Copilot Seats

- Adjustable Fore and Aft

Seat Belts and Shoulder Harness (all seats)

Wall to Wall Carpeting

Map and Storage Pockets

Luggage Compartment

EXTERIOR

Epoxy Corrosion Proofing, all structure

Lockable LH and RH Doors

Rear Window

All Windows Tinted

Tie Down Rings

Main Wheels. 5.00 x 5

Nose Wheel, 4.00 x 6

EXTERIOR LIGHTS

Vertical Tail Strobe

Taxi Light

Nav. Wing Lights with Strobe

Tail Light

POWERPLANT and **PROPELLER**

Engines - 1 ROTAX 912ULS2 100 HP,

4 Cylinders liquid/air cooled

Integrated Reduction Gear

Dual Ignition System

Dual Throttle Control

Tubular Steel Engine Mount

Propeller - fixed pitch

Propeller Spinner

Fire Sleeve on Fuel and Oil Lines

Air Filter

Oil Filter

Oil and Water Radiators

Thermostatic Oil Valve

PRODUCT SUPPORT / DOCUMENTS

Manufacturers Full 2 Year

Limited Warranty

Pilot Operating Handbook

Maintenance Manual











170 Aviation Way Watsonville, CA 95076 www.westcoastsportaircraft.com Phone 831.234.1049

