

QUALITY AIRCRAFT SINCE 1948

TECNAM

North America

P2008



ADVANTAGES

- Excellent Baggage Capacity
- Sleek Composite Fuselage
- Ideal Touring Aircraft with Spacious Interior and Quiet Cabin

MAIN CHARACTERISTICS / PERFORMANCE

ENGINE

Manufacturer	Rotax
Model	912ULS2/S2
Power	100 hp
Number of Cylinders	4

PROPELLER

Manufacturer	Tonini
Model	GT
Number of Blades	2
Type	Fixed

WEIGHTS

Maximum Take-off weight	1320 lbs.
Standard Equipped weight	780 lbs.
Standard Useful Load	540 lbs.
Limit Loads	+4/-2g
Ultimate Loads	+6/-3g

DIMENSION

Wing Span	28.9 ft.
Wing Area	150 sq. ft.
Fuselage Length	22.7 ft.
Fuselage Height	8.1 ft.
Cabin width	48 in.
Baggage Allowance	44 lbs.

SPEED

Max. at Sea Level, Gross Weight	120 kts
Cruise, 75% Power	112 kts
VNE	146 kts

STALL SPEED

Flaps up, Power off	45 kts
Flaps down, Power off	41 kts
Rate of Climb at Sea Level	900 ft/m
Service Ceiling	14,000 ft.
Takeoff run over 50 ft. Obstacle	700 ft.
Landing run over 50 ft. Obstacle	915 ft.
Demonstrated crosswind	17 kts

P2008

www.tecnam.net

P2008

Standard Equipment

FLIGHT INSTRUMENTS and INDICATORS

Magnetic Compass
Airspeed Indicator - Kts
Altimeter Dual Mode - IN/Mb
Vertical Speed
Bank Indicator
Flap Indicator
Pitot System
Static System
Stabilator Trim Position Indicator

ENGINE INSTRUMENTS

Tachometer
Hour Recorder
Oil Pressure
Oil Temperature
Cylinder Head Temperature
Fuel Pressure

OTHER INSTRUMENTS

Voltmeter
Ammeter
LH + RH Fuel Quantity
O.A.T.
ELT AK-450 Ameri King

FLIGHT CONTROLS

Hydraulic Toe Brakers
Parking Brake
Electric Flaps
Dual Flight Controls
Castering or Steerable Nose Wheel
Stabilator Trim (electrically acuated from stick)
Engine Controls

- Central Quadrant with single throttle lever
- Choke

Flight Trim Controls

- Stabilator (electrically acuated from stick)

Fuel Control Selection Andair
Panel Switches

- Split Master Switch
- Avionics Master

Starter Key

ELECTRONIC SYSTEM

12 Volt 18 Amp. Hour Battery
12 Volt Alternator - 20 Amp.
Switches

- Landing Light
- Strobe Light
- Nav. Light

12 Volt Socket
Circuit Breaker Panel

FUEL SYSTEM

2 Integral Fuel Tanks (24.3 gal. total)
Total Capacity

- Engine Driven Fuel Pump
- Fuel Quick Drains

Fuel Gascolator

INTERIOR

Pilot and Copilot Seats

- Adjustable Fore and Aft
- Arm Rest

Seat Belts and Shoulder Harness (all seats)
Wall to Wall Carpeting
Map and Storage Pockets
Roomy Luggage Compartments
Heating System with Defrost

EXTERIOR

Composite Fuselage and Vertical Stabilizer
Epoxy Corrosion Proofing on all metal surfaces
Lockable LH and RH Doors
All Windows Tinted
Tie Down Rings
Main Wheels, 5.00 x 5
Nose Wheel, 4.00 x 5

EXTERIOR LIGHTS

Vertical Tail Strobe
Taxi Light
Nav. Wing Lights with Strobe

POWERPLANT and PROPELLER

Engines - 1 ROTAX 912ULS2 100 HP,
4 Cylinders liquid/air cooled
Integrated Reduction Gear
Dual Ignition System
Dual Throttle Control
Tubular Steel Engine Mount
Propeller - Fixed Pitch
Propeller Spinner
Fire Sleeve on Fuel and Oil Lines
Air Filter
Oil Filter
Oil and Water Radiators
Thermostatic Oil Valve

PRODUCT SUPPORT / DOCUMENTS

Manufacturers Full 2 Year
Limited Warranty
Pilot Operating Handbook
Maintenance Manual




west coast sport aircraft, inc.

170 Aviation Way Watsonville, CA 95076

www.westcoastsporaircraft.com

Phone 831.234.1049

